

Robert Herriot (editor)  
Sun Microsystems  
Sylvan Butler  
Hewlett-Packard  
Paul Moore  
Microsoft.  
Randy Turner  
Sharp Labs  
November 7, 1997

Internet Printing Protocol/1.0: Protocol Specification  
draft-ietf-ipp-protocol-032.txt  
Copyright © The Internet Society (date). All Rights Reserved.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44

Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress".

To learn the current status of any Internet-Draft, please check the "lid-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), nic.nordu.net (Europe), munnari.oz.au (Pacific Rim), ds.internic.net (US East Coast), or ftp.isi.edu (US West Coast).

Abstract

This document is one of a set of documents, which together describe all aspects of a new Internet Printing Protocol (IPP). IPP is an application level protocol that can be used for distributed printing using Internet tools and technology. The protocol is heavily influenced by the printing model introduced in the Document Printing Application (ISO/IEC 10175 DPA) standard [dpa]. Although DPA specifies both end user and administrative features, IPP version 1.0 is focused only on end user functionality.

The full set of IPP documents includes:

- ~~Internet Printing Protocol: Requirements~~
- Requirements for an Internet Printing Protocol [ipp-req]
- Internet Printing Protocol/1.0: Model and Semantics [ipp-mod]
- Internet Printing Protocol/1.0: Protocol Specification (this document)

The requirements document takes a broad look at distributed printing functionality, and it enumerates real-life scenarios that help to clarify the features that need to be included in a printing protocol for the Internet. It identifies requirements for three types of users: end users, operators, and administrators. The requirements document calls out a subset of end user requirements that MUST be satisfied in the first version of IPP. Operator and administrator requirements are out of scope for v1.0. The model and semantics document describes a simplified model with abstract objects, their attributes, and their operations. The model introduces a Printer object and a Job object. The Job object supports multiple documents per job. The protocol specification is formal document which incorporates the ideas in all the other documents into a concrete mapping using clearly defined data representations and transport protocol mappings that real implementers can use to develop interoperable client and printer (server) side components.

This document is the "Internet Printing Protocol/1.0: Protocol Specification" document.

Notice

45 The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary  
46 rights which may cover technology that may be required to practice this standard. Please address the information to the IETF  
47 Executive Director.

48 Copyright © The Internet Society (date). All Rights Reserved.

49 This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise  
50 explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without  
51 restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative  
52 works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to  
53 the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which  
54 case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into  
55 languages other than English.

56 The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

57 This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND  
58 THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING  
59 BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE  
60 ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR  
61 PURPOSE.

## 62 Table of Contents

63	1. Introduction .....	4
64	2. Conformance Terminology .....	4
65	3. Encoding of the Operation Layer.....	4
66	3.1 Picture of the Encoding .....	4
67	3.2 Syntax of Encoding .....	6
68	3.3 Version .....	7
69	3.4 Mapping of Operations .....	7
70	3.5 Mapping of Status-code .....	8
71	3.6 Tags .....	8
72	3.6.1 Delimiter Tags .....	8
73	3.6.2 Value Tags.....	9
74	3.7 Name-Lengths.....	10
75	3.8 Mapping of Attribute Names.....	10
76	3.9 Value Lengths .....	11
77	3.10 Mapping of Attribute Values.....	11
78	3.11 Data .....	12
79	4. Encoding of Transport Layer .....	12
80	4.1 General Headers .....	13
81	4.2 Request Headers.....	14
82	4.3 Response Headers .....	14
83	4.4 Entity Headers.....	15
84	5. Security Considerations .....	15
85	6. Copyright.....	16
86	7. References .....	16
87	8. Author's Address.....	17
88	9. Other Participants: .....	18
89	10. Appendix A: Protocol Examples .....	18
90	10.1 Print-Job Request .....	18
91	10.2 Print-Job Response (successful).....	19
92	10.3 Print-Job Response (failure).....	20
93	10.4 Print-URI Request.....	20
94	10.5 Create-Job Request .....	21
95	10.6 Get-Jobs Request.....	22
96	10.7 Get-Jobs Response .....	22
97	11. Appendix B: Mapping of Each Operation in the Encoding .....	23
98	12. Appendix C: Hints to implementors using IPP with SSL3 .....	26
99		
100		
101		

## 102 1. Introduction

103 This document contains the rules for encoding IPP operations and describes two layers: the transport layer and the operation  
104 layer.

105 The transport layer consists of an HTTP/1.1 request or response. RFC 2068 [rfc2068] describes HTTP/1.1. This document  
106 specifies the HTTP headers that an IPP implementation supports.

107 The operation layer consists of a message body in an HTTP request or response. The document "Internet Printing Protocol/1.0:  
108 Model and Semantics" [ipp-mod] defines the semantics of such a message body and the supported values. This document  
109 specifies the encoding of an IPP operation. The aforementioned document [ipp-mod] is henceforth referred to as the "IPP model  
110 document"

## 111 2. Conformance Terminology

112 The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT",  
113 "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [rfc2119].

## 114 3. Encoding of the Operation Layer

115 The operation layer SHALL contain a single operation request or operation response.

116 The encoding consists of octets as the most primitive type. There are several types built from octets, but ~~three~~ two important types  
117 are integers, ~~and~~ character strings and octet strings, on which most other data types are built. Every character string in this  
118 encoding SHALL be a sequence of characters where the characters are associated with some charset and some natural language,  
119 ~~member of the UCS-2 coded character set.~~ A character string MUST be in "network byte order" with the first character in the  
120 value (according to reading order) being the first character in the encoding. A character string whose associated charset is US-  
121 ASCII whose associated natural language is US English is henceforth called a US-ASCII-STRING. A character string whose  
122 associated charset and natural language are specified in a request or response as described in the model document is henceforth  
123 called a LOCALIZED-STRING. ~~and SHALL be encoded using UTF-8 which uses 1 to 3 octets per character.~~ An octet string  
124 MUST be in "network byte order" with the first octet in the value (according to reading order) being the first octet in the  
125 encoding. Every integer in this encoding SHALL be encoded as a signed integer using two's-complement binary encoding with  
126 big-endian format (also known as "network order" and "most significant byte first"). The number of octets for an integer SHALL  
127 be 1, 2 or 4, depending on usage in the protocol. Such one-octet integers, henceforth called SIGNED-BYTE, are used for the  
128 version and tag fields. Such two-byte integers, henceforth called SIGNED-SHORT are used for the operation, status-code and  
129 length fields. Four byte integers, henceforth called SIGNED-INTEGER, are used for values fields.

130 The following two sections present the operation layer in two ways

- 131 • informally through pictures and description
- 132 • formally through Augmented Backus-Naur Form (ABNF), as specified by draft-ietf-drums-abnf-02.txt [abnf]

### 133 3.1 Picture of the Encoding

134 The encoding for an operation request or response consists of:

135	-----		
136		version	2 bytes - required
137	-----		
138		operation (request) or status-code (response)	2 bytes - required
139	-----		
140		xxx-attributes-tag	1 byte
141	-----		-0 or more
142		xxx-attribute-sequence	n bytes
143	-----		
144		data-tag	1 byte - required
145	-----		
146		data	q bytes - optional
147	-----		

148 The xxx-attributes-tag and xxx-attribute-sequence represents four different values of “xxx”, namely, operation, job, printer and  
 149 unsupported-job. The xxx-attributes-tag and xxx-attribute-sequence may be omitted if the operation has no attributes or it may be  
 150 repeated with the same or different values of “xxx” in ways that are specific to each operation. The data is omitted from some  
 151 operations, but the data-tag is present even when the data is omitted. Note, the xxx-attributes-tags and data-tag are called  
 152 ‘delimiter-tags’.

153 Note: the xxx-attribute-sequence, shown above may consist of 0 bytes, according to the rule below.

154 An xxx-attributes-sequence consists of zero or more compound-attributes.

155	-----		
156		compound-attribute	s bytes - 0 or more
157	-----		

158 A compound-attribute consists of an attribute with a single value followed by zero or more additional values.

159 Note: a ‘compound-attribute’ represents a single attribute in the model document. The ‘additional value’ syntax is for attributes  
 160 with 2 or more values.

161 Each attribute consists of:

162	-----		
163		value-tag	1 byte
164	-----		
165		name-length (value is u)	2 bytes
166	-----		
167		name	u bytes
168	-----		
169		value-length (value is v)	2 bytes
170	-----		
171		value	v bytes
172	-----		

173 An additional value consists of:

174	-----		
175		value-tag	1 byte
176	-----		
177		name-length (value is 0x0000)	2 bytes
178	-----		
179		value-length (value is w)	2 bytes
180	-----		
181		value	w bytes
182	-----		
183			-0 or more

184 Note: an additional value is like an attribute whose name-length is 0.

185 From the standpoint of a parsing loop, the encoding consists of:

186	-----		
187		version	2 bytes - required
188	-----		
189		operation (request) or status-code (response)	2 bytes - required
190	-----		
191		tag (delimiter-tag or value-tag)	1 byte
192	-----		
193		empty or rest of attribute	x bytes
194	-----		
195		data-tag	2 bytes - required
196	-----		
197		data	y bytes - optional
198	-----		
199			-0 or more

200 The value of the tag determines whether the bytes following the tag are:

- 201 • attributes
- 202 • data
- 203 • the remainder of a single attribute where the tag specifies the type of the value.

### 204 3.2 Syntax of Encoding

205 The syntax below is ABNF [abnf] except 'strings of literals' SHALL be case sensitive. For example 'a' means lower case 'a' and  
 206 not upper case 'A'. In addition, SIGNED-BYTE and SIGNED-SHORT fields are represented as '%x' values which show their  
 207 range of values.

```

208 ipp-message = ipp-request / ipp-response
209 ipp-request = version operation
210              *(xxx-attributes-tag xxx-attribute-sequence) data-tag data
211 ipp-response = version status-code
212              *(xxx-attributes-tag xxx-attribute-sequence) data-tag data
213 xxx-attribute-sequence = *compound-attribute
214 ; where "xxx" in the three rules above stands for any of the following
215 ; values: "operation", "job", "printer" or "unsupported-job".
216
217
218 version = major-version minor-version
219 major-version = SIGNED-BYTE ; initially %d1
220 minor-version = SIGNED-BYTE ; initially %d0
  
```

221  
 222 operation = SIGNED-SHORT ; mapping from model defined below  
 223 status-code = SIGNED-SHORT ; mapping from model defined below  
 224  
 225 compound-attribute = attribute \*additional-values  
 226  
 227 attribute = value-tag name-length name value-length value  
 228 additional-values = value-tag zero-name-length value-length value  
 229  
 230 name-length = SIGNED-SHORT ; number of octets of 'name'  
 231 name = LALPHA \*( LALPHA / DIGIT / "-" / "\_" / "." )  
 232 value-length = SIGNED-SHORT ; number of octets of 'value'  
 233 value = OCTET-STRING  
 234  
 235 data = OCTET-STRING  
 236  
 237 zero-name-length = %x00.00 ; name-length of 0  
 238 operation-attributes-tag = %x01 ; tag of 1  
 239 job-attributes-tag = %x02 ; tag of 2  
 240 printer-attributes-tag = %x04 ; tag of 4  
 241 unsupported-job-attributes-tag = %x05 ; tag of 5  
 242 data-tag = %x03 ; tag of 3  
 243 value-tag = %x10-FF  
 244  
 245 SIGNED-BYTE = BYTE  
 246 SIGNED-SHORT = 2BYTE  
 247 DIGIT = %x30-39 ; "0" to "9"  
 248 LALPHA = %x61-7A ; "a" to "z"  
 249 BYTE = %x00-FF  
 250 OCTET-STRING = \*BYTE  
 251

252 The syntax allows an xxx-attributes-tag to be present when the xxx-attribute-sequence that follows is empty. The syntax is  
 253 defined this way to allow for the response of Get-Jobs where no attributes are returned for some job-objects. Although it is  
 254 RECOMMENDED that the sender not send an xxx-attributes-tag if there are no attributes (except in the Get-Jobs response just  
 255 mentioned), the receiver MUST be able to decode such syntax.

### 256 3.3 Version

257 The version SHALL consist of a major and minor version, each of which SHALL be represented by a SIGNED-BYTE. The  
 258 protocol described in this document SHALL have a major version of 1 (0x01) and a minor version of 0 (0x00). The ABNF for  
 259 these two bytes SHALL be %x01.00.

### 260 3.4 Mapping of Operations

261 Operations are defined as enums in the model document. An operations enum value SHALL be encoded as a SIGNED-SHORT

262 Note: the values 0x4000 to 0xFFFF are reserved for private extensions.

## 263 3.5 Mapping of Status-code

264 Status-codes are defined as enums in the model document. A status-code enum value SHALL be encoded as a SIGNED-SHORT

265 If an IPP status-code is returned, then the HTTP Status-Code MUST be 200 (OK). With any other HTTP Status-Code value, the  
266 HTTP response SHALL NOT contain an IPP message-body, and thus no IPP status-code is returned.

## 267 3.6 Tags

268 There are two kinds of tags:

- 269 • delimiter tags: delimit major sections of the protocol, namely attributes and data
- 270 • value tags: specify the type of each attribute value

### 271 3.6.1 Delimiter Tags

272 The following table specifies the values for the delimiter tags:

Tag Value (Hex)	Delimiter
0x00	reserved
0x01	operation-attributes-tag
0x02	job-attributes-tag
0x03	data-tag
0x04	printer-attributes-tag
0x05	unsupported-job-attributes-tag
0x06-0x0F	reserved for future delimiters

273

274 When an xxx-attributes-tag occurs in the protocol, it SHALL mean that the zero or more following attributes up to the next  
275 delimiter tag are xxx attributes as defined in the model document, where xxx is operation, job, printer, unsupported-job.

276 Doing substitution for xxx in the above paragraph, this means the following. When an operation-attributes-tag occurs in the  
277 protocol, it SHALL mean that the zero or more following attributes up to the next delimiter tag are operation attributes as defined  
278 in the model document. When an job-attributes-tag occurs in the protocol, it SHALL mean that the zero or more following  
279 attributes up to the next delimiter tag are job attributes as defined in the model document. When an printer-attributes-tag occurs in  
280 the protocol, it SHALL mean that the zero or more following attributes up to the next delimiter tag are printer attributes as  
281 defined in the model document. When an unsupported-job-attributes-tag occurs in the protocol, it SHALL mean that the zero or  
282 more following attributes up to the next delimiter tag are unsupported-job attributes as defined in the model document.

283 The operation-attributes-tag and data-tag SHALL each occur exactly once in an operation. The operation-attributes-tag SHALL  
284 be the first tag delimiter, and the data-tag SHALL be the last tag delimiter.

285 Each of the ~~other three~~ ~~four~~ xxx-attributes-tags defined above is OPTIONAL in an operation and each SHALL occur at most  
286 once in an operation, except for job-attributes-tag in a Get-Jobs response which may occur zero or more times.

287 ~~The data-tag SHALL occur exactly once in an operation. If an operation contains an operations-attribute-tag, it SHALL be the~~  
288 ~~first tag delimiter. The data-tag SHALL be the last tag delimiter.~~

289 The order and presence of delimiter tags for each operation request and each operation response SHALL be that defined in the  
290 model document. For further details, see Section 3.8 Mapping of Attribute Names and Appendix B: Mapping of Each Operation  
291 in the Encoding.



## 292 3.6.2 Value Tags

293 The remaining tables show values for the value-tag, which is the first octet of an attribute. The value-tag specifies the type of the  
 294 value of the attribute. If the value-tag specifies a type of compoundValue, it represents a compound value whose type is the that  
 295 of the last member of the compound value. The value of the value-tag of an attribute SHALL either be a type value specified in  
 296 the model document or an “out-of-band” value, such as “unsupported” or “default”. If the value of value-tag for an attribute is  
 297 not “out-of-band” and differs from the value type specified by the model document, then a printer receiving such a request MAY  
 298 reject the attribute or just the value. A client receiving such a response MAY ignore the attribute or just the value.

299 If ipp-attribute-fidelity is true and a printer rejects a value, it is the same as rejecting the attribute. If ipp-attribute-fidelity is false  
 300 and a printer rejects a value, or it a client rejects a value, then it is as if the attribute didn't have that value. If after rejecting  
 301 values, the attribute no longer has any values the attribute is rejected.

302 Note: the intent of the above rule is for servers to be able to understand text and name values when they don't support the  
 303 naturalLanguage override for the value.

304 The following table specifies the “out-of-band” values for the value-tag.

Tag Value (Hex)	Meaning
0x10	unsupported
0x11	<u>reserved for future ‘default’</u>
0x12	<u>unknownno-value</u>
0x13	compoundValue
0x14-0x1F	reserved for future “out-of-band” values.

305 The “unsupported” value SHALL be used in the attribute-sequence of an error response for those attributes which the printer does  
 306 not support. The “default” value is reserved for future use of setting value back to their default value. The “unknownno-value”  
 307 value is used for the value of a supported attribute when its value is temporarily unknown. ~~the “no-value” value in model, e.g.~~  
 308 ~~when a document attribute is returned as a set of values and an attribute has no specified value for one or more of the documents.~~  
 309 The “compoundValue” SHALL be used to form a single value from a collection of values, and its value is the number of  
 310 members forming the compound value, excluding the compoundValue. For example, a text value with a naturalLanguage  
 311 override consists of 3 “values”: a compoundValue with value 2, a naturalLanguage value and a text value.

312 The following table specifies the integer values for the value-tag

Tag Value (Hex)	Meaning
0x20	reserved
0x21	integer
0x22	boolean
0x23	enum
0x24-0x2F	reserved for future integer types

313 NOTE: 0x20 is reserved for “generic integer” if should ever be needed.

314 The following table specifies the octetString values for the value-tag

Tag Value (Hex)	Meaning
0x30	octetString with an unspecified format
0x31	dateTime
0x32	resolution

Tag Value (Hex)	Meaning
0x33	rangeOfInteger
0x34	reserved for dictionary (in the future)
0x35-0x3F	reserved for future octetString types

315 The following table specifies the character-string values for the value-tag

Tag Value (Hex)	Meaning
0x40	reserved
0x41	text
0x42	name
0x43	reserved
0x44	keyword
0x45	uri
0x46	uriScheme
0x47	charSet
0x48	naturalLanguage
0x49	mimeMediaType
0x4A-0x5F	reserved for future character string types

316 NOTE: 0x40 is reserved for “generic character-string” if should ever be needed.

317 The values 0x60-0xFF are reserved for future types. There are no values allocated for private extensions. A new type must be  
318 registered via the type 2 process.

### 319 3.7 Name-Lengths

320 The name-length field SHALL consist of a SIGNED-SHORT. This field SHALL specify the number of octets in the name field  
321 which follows the name-length field, excluding the two bytes of the name-length field.

322 If a name-length field has a value of zero, the following name field SHALL be empty, and the following value SHALL be treated  
323 as an additional value for the preceding attribute. Within an attribute-sequence, if two attributes have the same name, the first  
324 occurrence SHALL be ignored. The zero-length name is the only mechanism for multi-valued attributes.

### 325 3.8 Mapping of Attribute Names

326 Some attributes are encoded in a special position. These attribute are:

- 327 • “printer-uri”: The target printer-uri of each operation in the IPP model document SHALL be specified outside of the  
328 operation layer as the request-URI on the Request-Line at the HTTP level.
- 329 • “job-uri”: The target job-uri of each operation in the IPP model document SHALL be specified outside of the operation  
330 layer as the request-URI on the Request-Line at the HTTP level.
- 331 • “document-content”: The attribute named “document-content” in the IPP model document SHALL become the “data”  
332 in the operation layer.
- 333 • “status-code”: The attribute named “status-code” in the IPP model document SHALL become the “status-code” field in  
334 the operation layer response.

335 The model document arranges the remaining attributes into groups for each operation request and response. Each such group  
336 SHALL be represented in the protocol by an xxx-attribute-sequence preceded by the appropriate xxx-attributes-tag (See the table

337 below and Appendix B: Mapping of Each Operation in the Encoding). In addition, the order of these xxx-attributes-tags and xxx-  
 338 attribute-sequences in the protocol SHALL be the same as in the model document, but the order of attributes within each xxx-  
 339 attribute-sequence SHALL be unspecified. The table below maps the model document group name to xxx-attributes-sequence

Model Document Group	xxx-attributes-sequence
Operation Attributes	operations-attributes-sequence
Job Template Attributes	job-attributes-sequence
Job Object Attributes	job-attributes-sequence
Unsupported Attributes	unsupported-job-attributes-sequence
Requested Attributes (Get-Attributes of job object)	job-attributes-sequence
Requested Attributes (Get-Attributes of printer object)	printer-attributes-sequence
Document Content	in a special position as described above

340 ISSUE: coordinate this with the model document.

341 If an operation contains attributes from more than one job object (e.g. Get-Jobs response), the attributes from each job object  
 342 SHALL be in a separate job-attribute-sequence, such that the attributes from the ith job object are in the ith job-attribute-  
 343 sequence. See Section 11 "Appendix B: Mapping of Each Operation in the Encoding" for table showing the application of the  
 344 rules above.

### 345 3.9 Value Lengths

346 Each attribute value SHALL be preceded by a SIGNED-SHORT which SHALL specify the number of octets in the value which  
 347 follows this length, exclusive of the two bytes specifying the length.

348 For any of the types represented by binary signed integers, the sender MUST encode the value in exactly four octets..

349 For any of the types represented by character-strings, the sender MUST encode the value with all the characters of the string and  
 350 without any padding characters.

351 If a value-tag contains an "out-of-band" value which is not compoundValue, such as "unsupported", the value-length SHALL be  
 352 0 and the value empty — the value has no meaning when the value-tag has an "out-of-band" value. If a printer or client receives  
 353 an operation with a nonzero value-length in this case, it SHALL ignore the value field.

### 354 3.10 Mapping of Attribute Values

355 ~~The following SHALL be the mapping of attribute values to their IPP encoding in the value field. The syntax types and most of~~  
 356 ~~the details of their representation~~ are defined in the IPP model document. The table below augments the information in the model  
 357 document, and defines the syntax types from the model document in terms of the 5 basic types defined in section 3 Encoding of  
 358 the Operation Layer. The 5 types are US-ASCII-STRING, LOCALIZED-STRING, SIGNED-INTEGER, SIGNED-SHORT,  
 359 SIGNED-BYTE, and OCTET-STRING.

Syntax of Attribute Value	Encoding
---------------------------	----------

<u>text, name</u>	<u>LOCALIZED-STRING.</u>
-------------------	--------------------------

The override natural language mechanism is encoded by syntactically preceding the text or name value by two values: first a value of type compoundValue whose value is 2 and second a value of type naturalLanguage whose value is the language override. From a protocol syntax view, there are three separate values: the compoundValue, the naturalLanguage value and the text or name value, but from a semantic view, the Printer treats them as a single value where the naturalLanguage value overrides the language of

<b>Syntax of Attribute Value</b>	<b>Encoding</b>
	<u>the immediately following text or name value in the attribute. The override applies to just the text or name within the compound value. Other text or name values needing an override must be overridden with additional compoundValues.</u>
<u>charset, naturalLanguage, mimeType, keyword, uri, and uriScheme</u>	<u>US-ASCII-STRING</u>
boolean	<u>SIGNED-BYTE one binary octet where 0x00 is 'false' and 0x01 is 'true'</u>
integer and enum	<u>a SIGNED-INTEGER, defined previously as a signed integer using two's complement binary encoding in four octets with big-endian format (also known as "network order" and "most significant byte first").</u>
compoundValue	<u>a SIGNED-INTEGER with a special meaning. has the same representation as an integer, but with a different meaning. If the value of a compoundValue is n, then the n following values of the attribute form a single value whose type is that of the last member of the compound value. For example, if an attribute has 3 successive values: compoundValue of 2, naturalLanguage of 'fr-CA' and name of 'chien', then these three "values" form a single value which is a name of 'chien' in Canadian French.</u>
dateTime	<u>OCTET-STRING consisting of eleven octets whose contents are defined by "DateAndTime" in RFC 1903 [rfc1903]. Although RFC 1903 also defines an eight octet format which omits the time zone, a value of this type in the IPP protocol MUST use the eleven octet format. [ transfer to model].</u>
resolution	<u>OCTET STRING consisting of nine octets consisting of 2 SIGNED-INTEGERS followed by a SIGNED-BYTE. The values are the same as those specified in RFC 1759 (Printer MIB) [r1759]. The first SIGNED-INTEGER contains the value of <u>cross feed direction resolution prtMarkerAddressabilityXFeedDir</u>. The second SIGNED-INTEGER contains the value of <u>feed direction resolution prtMarkerAddressabilityFeedDir</u>. The SIGNED-BYTE contains the <u>units value of prtMarkerAddressabilityUnit</u>. Note: the latter value is either 3 (tenThousandsOfInches) or 4 (micrometers) and the addressability is in 10,000 units of measure. Thus the SIGNED-INTEGERS represent integral values in either dots-per-inch or dots-per-centimeter.</u>
rangeOfInteger	<u>Eight octets consisting of 2 SIGNED-INTEGERS. The first SIGNED-INTEGERS contains the <u>lowerest bound value of the range</u> and the second SIGNED-INTEGERS contains the <u>upper highest bound value of the range</u></u>
1setOf X	<u>encoding according to the rules for an attribute with more than <u>1</u> more value. Each value X is encoded according to the rules for encoding its type.</u>
<u>octetString</u>	<u>OCTET-STRING</u>

360 The type of the value in the model document determines the encoding in the value and the value of the value-tag.

### 361 3.11 Data

362 The data part SHALL include any data required by the operation

## 363 4. Encoding of Transport Layer

364 HTTP/1.1 shall be the transport layer for this protocol.

365 The operation layer has been designed with the assumption that the transport layer contains the following information:

- 366       • the URI of the target job or printer operation  
 367       • the total length of the data in the operation layer, either as a single length or as a sequence of chunks each with a length.  
 368 It is REQUIRED that a printer support HTTP over port 80, though a printer may support HTTP over port 516 or some other port.  
 369 In addition, a printer may have to support another port for secure connections.

370 Note: Consistent with RFC 2068 (HTTP/1.1), HTTP URI's for IPP implicitly reference port 80. If a URI references some other  
 371 port, the port number must be explicitly specified in the URI.

372 Each HTTP operation shall use the POST method where the request-URI is the object target of the operation, and where the  
 373 "Content-Type" of the message-body in each request and response shall be "application/ipp". The message-body shall contain the  
 374 operation layer and shall have the syntax described in section 3.2 "Syntax of Encoding". A client implementation SHALL adhere  
 375 to the rules for a client described in RFC 2068 [rfc2068]. A printer (server) implementation SHALL adhere the rules for an origin  
 376 server described in RFC 2068. In the following sections, there are a tables of all HTTP headers which describe their use in an IPP  
 377 client or server. The following is an explanation of each column in these tables.

- 378       • the "header" column contains the name of a header
- 379       • the "request/client" column indicates whether a client sends the header.
- 380       • the "request/ server" column indicates whether a server supports the header when received.
- 381       • the "response/ server" column indicates whether a server sends the header.
- 382       • the "response /client" column indicates whether a client supports the header when received.
- 383       • the "values and conditions" column specifies the allowed header values and the conditions for the header to be present in  
 384 a request/response.

385 The table for "request headers" does not have columns for responses, and the table for "response headers" does not have columns  
 386 for requests.

387 The following is an explanation of the values in the "request/client" and "response/ server" columns.

- 388       • **must:** the client or server MUST send the header,
- 389       • **must-if:** the client or server MUST send the header when the condition described in the "values and conditions" column  
 390 is met,
- 391       • **may:** the client or server MAY send the header
- 392       • **not:** the client or server SHOULD NOT send the header. It is not relevant to an IPP implementation.

393 The following is an explanation of the values in the "response/client" and "request/ server" columns.

- 394       • **must:** the client or server MUST support the header,
- 395       • **may:** the client or server MAY support the header
- 396       • **not:** the client or server SHOULD NOT support the header. It is not relevant to an IPP implementation.

## 397 4.1 General Headers

398 The following is a table for the general headers.

399 ISSUE: an HTTP expert should review these tables for accuracy.

General-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
Cache-Control	must	not	must	not	"no-cache" only
Connection	must-if	must	must-if	must	"close" only. Both client and server SHOULD keep a connection for the

General-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
					duration of a sequence of operations. The client and server MUST include this header for the last operation in such a sequence.
Date	may	may	must	may	per RFC 1123 [rfc1123]
Pragma	must	not	must	not	“no-cache” only
Transfer-Encoding	must-if	must	must-if	must	“chunked” only . Header MUST be present if Content-Length is absent.
Upgrade	not	not	not	not	
Via	not	not	not	not	

400

## 401 4.2 Request Headers

402 The following is a table for the request headers.

403

Request-Header	Client	Server	Request Values and Conditions
Accept	may	must	“application/ipp” only. This value is the default if the client omits it
Accept-Charset	not	not	Charset information is within the application/ipp entity empty and per RFC 2068 [rfc2068] and IANA registry for content-codings
Accept-Encoding	may	must	. language information is within the application/ipp entity per RFC 2068. A client MUST send this header when it receives a 401 “Unauthorized” response and does not receive a “Proxy-Authenticate” header.
Accept-Language	not	not	per RFC 2068. Because RFC recommends sending this header only with the user’s approval, it is not very useful per RFC 2068
Authorization	must-if	must	
From	not	not	
Host	must	must	
If-Match	not	not	
If-Modified-Since	not	not	
If-None-Match	not	not	
If-Range	not	not	
If-Unmodified-Since	not	not	
Max-Forwards	not	not	
Proxy-Authorization	must-if	not	per RFC 2068. A client MUST send this header when it receives a 401 “Unauthorized” response and a “Proxy-Authenticate” header.
Range	not	not	
Referer	not	not	
User-Agent	not	not	

## 404 4.3 Response Headers

405 The following is a table for the request headers.

406

Response-Header	Server	Client	Response Values and Conditions
-----------------	--------	--------	--------------------------------

Response-Header	Server	Client	Response Values and Conditions
Accept-Ranges	not	not	
Age	not	not	
Location	must-if	may	per RFC 2068. When URI needs redirection.
Proxy-Authenticate	not	must	per RFC 2068
Public	may	may	per RFC 2068
Retry-After	may	may	per RFC 2068
Server	not	not	
Vary	not	not	
Warning	may	may	per RFC 2068
WWW-Authenticate	must-if	must	per RFC 2068. When a server needs to authenticate a client.

#### 407 4.4 Entity Headers

408 The following is a table for the entity headers.

409

Entity-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
Allow	not	not	not	not	
Content-Base	not	not	not	not	
Content-Encoding	may	must	must	must	per RFC 2068 and IANA registry for content codings.
Content-Language	not	not	not	not	Application/ipp handles language
Content-Length	must-if	must	must-if	must	the length of the message-body per RFC 2068. Header MUST be present if Transfer-Encoding is absent..
Content-Location	not	not	not	not	
Content-MD5	may	may	may	may	per RFC 2068
Content-Range	not	not	not	not	
Content-Type	must	must	must	must	“application/ipp” only
ETag	not	not	not	not	
Expires	not	not	not	not	
Last-Modified	not	not	not	not	

#### 410 5. Security Considerations

411 When utilizing HTTP 1.1 as a transport of IPP, the security considerations outlined in RFC 2068 [rfc2068] apply. Specifically,  
 412 IPP servers can generate a 401 “Unauthorized” response code to request client authentication and IPP clients should correctly  
 413 respond with the proper “Authorization” header. Both Basic Authentication (RFC 2068) and Digest Authentication (RFC 2069)  
 414 [rfc2069] flavors of authentication SHALL be supported. The server chooses which type(s) of authentication to accept. Digest  
 415 Authentication is a more secure method, and is always preferred to Basic Authentication.

416 For secure communication (privacy in particular), IPP SHOULD be run using a secure communications channel. For this purpose  
 417 it is the intention to define standardization of IPP in combination with Transport Layer Security (TLS), currently under  
 418 development in the IETF, when the TLS specifications are agreed and on the IETF standards track.

419 As an intercept solution for secure communication, the Secure Socket Layer 3.0 (SSL3) could be used, but be warned that such  
 420 implementations may not be able to interoperate with a future standardized IPP and TLS solution. Appendix C gives some hints  
 421 to implementors wanting to use SSL3 as intercept solution.

422 It is possible to combine the techniques, HTTP 1.1 client authentication (either basic or digest) with a secure communications  
423 channel. Together the two are more secure than client authentication and they perform user authentication.

424 See further discussion of IPP security concepts in the model document [ipp-mod].

## 425 **6. Copyright**

426 This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise  
427 explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without  
428 restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative  
429 works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to  
430 the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which  
431 case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into  
432 languages other than English.

433 The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

434 This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND  
435 THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING  
436 BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE  
437 ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR  
438 PURPOSE.

## 439 **7. References**

- 440 [rfc822] Crocker, D., "Standard for the Format of ARPA Internet Text Messages", RFC 822, August 1982.
- 441 [rfc1123] Braden, S., "Requirements for Internet Hosts - Application and Support", RFC 1123, October, 1989,
- 442 [rfc1179] McLaughlin, L. III, (editor), "Line Printer Daemon Protocol" RFC 1179, August 1990.
- 443 [rfc1630] T. Berners-Lee, "Universal Resource Identifiers in WWW: A Unifying Syntax for the Expression of Names and  
444 Addresses of Objects on the Network as used in the World-Wide Web", RFC 1630, June 1994.
- 445 [rfc1759] Smith, R., Wright, F., Hastings, T., Zilles, S., and Gyllenskog, J., "Printer MIB", RFC 1759, March 1995.
- 446 [rfc1738] Berners-Lee, T., Masinter, L., McCahill, M., "Uniform Resource Locators (URL)", RFC 1738, December, 1994.
- 447 [rfc1543] Postel, J., "Instructions to RFC Authors", RFC 1543, October 1993.
- 448 [rfc1766] H. Alvestrand, "Tags for the Identification of Languages", RFC 1766, March 1995.
- 449 [rfc1903] J. Case, et al. "Textual Conventions for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC  
450 1903, January 1996.
- 451 [rfc2046] N. Freed & N. Borenstein, Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types. November  
452 1996. (Obsoletes RFC1521, RFC1522, RFC1590), RFC 2046.
- 453 [rfc2048] N. Freed, J. Klensin & J. Postel. Multipurpose Internet Mail Extension (MIME) Part Four: Registration Procedures.  
454 November 1996. (Format: TXT=45033 bytes) (Obsoletes RFC1521, RFC1522, RFC1590) (Also BCP0013), RFC  
455 2048.



- 456 [rfc2068] R Fielding, et al, "Hypertext Transfer Protocol – HTTP/1.1" RFC 2068, January 1997
- 457 [rfc2069] J. Franks, et al, "An Extension to HTTP: Digest Access Authentication" RFC 2069, January 1997
- 458 [rfc2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119 , March 1997
- 459 [rfc2184] N. Freed, K. Moore, "MIME Parameter Value and Encoded Word Extensions: Character Sets, Languages, and  
460 Continuations", RFC 2184, August 1997,
- 461 [abnf] D. Crocker et al., "Augmented BNF for Syntax Specifications: ABNF", draft-ietf-drums-abnf-04.txt.
- 462 [char] N. Freed, J. Postel: IANA CharSet Registration Procedures, Work in Progress (draft-freed-charset-reg-02.txt).
- 463 [dpa] ISO/IEC 10175 Document Printing Application (DPA), June 1996.
- 464 [iana] IANA Registry of Coded Character Sets: <ftp://ftp.isi.edu/in-notes/iana/assignments/character-sets>
- 465 [ipp-req] Wright, F. D., "Requirements for an Internet Printing Protocol:"
- 466 [ipp-mod] Isaacson, S, deBry, R, Hastings, T, Herriot, R, Powell, P, "Internet Printing Protocol/1.0: Model and Semantics"
- 467 [ssl] Netscape, The SSL Protocol, Version 3, (Text version 3.02) November 1996.

## 468 8. Author's Address

469

Robert Herriot (editor)  
Sun Microsystems Inc.  
901 San Antonio Road, MPK-17  
Palo Alto, CA 94303

Phone: 650-786-8995  
Fax: 650-786-7077  
Email: robert.herriot@eng.sun.com

Sylvan Butler  
Hewlett-Packard  
11311 Chinden Blvd.  
Boise, ID 83714

Phone: 208-396-6000  
Fax: 208-396-3457  
Email: sbutler@boi.hp.com

Paul Moore  
Microsoft  
One Microsoft Way  
Redmond, WA 98053

Phone: 425-936-0908  
Fax: 425-93MS-FAX  
Email: paulmo@microsoft.com

Randy Turner  
Sharp Laboratories  
5750 NW Pacific Rim Blvd  
Camas, WA 98607

Phone: 360-817-8456  
Fax: : 360-817-8436  
Email: rturner@sharplabs.com

IPP Mailing List: [ipp@pwg.org](mailto:ipp@pwg.org)  
IPP Mailing List Subscription: [ipp-request@pwg.org](mailto:ipp-request@pwg.org)  
IPP Web Page: <http://www.pwg.org/ipp/>

470

471

## 9. Other Participants:

Chuck Adams - Tektronix	Harry Lewis - IBM
Ron Bergman - Data Products	Tony Liao - Vivid Image
Keith Carter - IBM	David Manchala - Xerox
Angelo Caruso - Xerox	Carl-Uno Manros - Xerox
Jeff Copeland - QMS	Jay Martin - Underscore
Roger Debry - IBM	Larry Masinter - Xerox
Lee Farrell - Canon	Ira McDonald, Xerox
Sue Gleeson - Digital	Bob Pentecost - Hewlett-Packard
Charles Gordon - Osicom	Patrick Powell - SDSU
Brian Grimshaw - Apple	Jeff Rackowitz - Intermec
Jerry Hadsell - IBM	Xavier Riley - Xerox
Richard Hart - Digital	Gary Roberts - Ricoh
Tom Hastings - Xerox	Stuart Rowley - Kyocera
Stephen Holmstead	Richard Schneider - Epson
Zhi-Hong Huang - Zenographics	Shigern Ueda - Canon
Scott Isaacson - Novell	Bob Von Anandel - Allegro Software
Rich Lomicka - Digital	William Wagner - Digital Products
David Kellerman - Northlake Software	Jasper Wong - Xionics
Robert Kline - TrueSpectra	Don Wright - Lexmark
Dave Kuntz - Hewlett-Packard	Rick Yardumian - Xerox
Takami Kurono - Brother	Lloyd Young - Lexmark
Rich Landau - Digital	Peter Zehler - Xerox
Greg LeClair - Epson	Frank Zhao - Panasonic
	Steve Zilles - Adobe

472

## 10. Appendix A: Protocol Examples

473

### 10.1 Print-Job Request

474

The following is an example of a Print-Job request with job-name, copies, and sides specified.

Octets	Symbolic Value	Protocol field
0x0100	1.0	version
0x0002	PrintJob	operation
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
US-ASCII	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value
0x42	name type	value-tag
0x0008		name-length
job-name	job-name	name

Octets	Symbolic Value	Protocol field
0x0006		value-length
foobar	foobar	value
0x02	start job-attributes	job-attributes-tag
0x21	integer type	value-tag
0x0005		name-length
copies	copies	name
0x0004		value-length
0x00000014	20	value
0x44	keyword type	value-tag
0x0005		name-length
sides	sides	name
0x0013		value-length
two-sided-long-edge	two-sided-long-edge	value
0x03	start-data	data-tag
%!PS...	<PostScript>	data

## 475 10.2 Print-Job Response (successful)

476 Here is an example of a Print-Job response which is successful:

Octets	Symbolic Value	Protocol field
0x0100	1.0	version
0x0000	OK (successful)	status-code
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
US-ASCII	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value
0x41	text type	value-tag
0x000E		name-length
status-message	status-message	name
0x0002		value-length
OK	OK	value
0x02	start job-attributes	job-attributes-tag
0x21	integer	value-tag
0x0007		name-length
job-id	job-id	name
0x0004		value-length
147	147	value
0x45	uri type	value-tag
0x0008		name-length
job-uri	job-uri	name
0x000E		value-length
http://foo/123	http://foo/123	value

Octets	Symbolic Value	Protocol field
0x25	name type	value-tag
0x0008		name-length
job-state	job-state	name
0x0001		value-length
0x03	pending	value
0x03	start-data	data-tag

### 477 10.3 Print-Job Response (failure)

478 Here is an example of a Print-Job response which fails because the printer does not support sides and because the value 20 for  
479 copies is not supported:

Octets	Symbolic Value	Protocol field
0x0100	1.0	version
0x0400	client-error-bad-request	status-code
0x01	start operation-attributes	operation-attribute tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
US-ASCII	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value
0x41	text type	value-tag
0x000E		name-length
status-message	status-message	name
0x000D		value-length
bad-request	bad-request	value
0x04	start unsupported-job-attributes	unsupported-job-attributes-tag
0x21	integer type	value-tag
0x0005		name-length
copies	copies	name
0x0004		value-length
0x00000014	20	value
0x10	unsupported (type)	value-tag
0x0005		name-length
sides	sides	name
0x0000		value-length
0x03	start-data	data-tag

### 480 10.4 Print-URI Request

481 The following is an example of Print-URI request with copies and job-name parameters.

Octets	Symbolic Value	Protocol field
0x0100	1.0	version
0x0003	Print-URI	operation

<b>Octets</b>	<b>Symbolic Value</b>	<b>Protocol field</b>
0x01	start operation-attributes	operation-attributes_tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
US-ASCII	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value
0x45	uri type	value-tag
0x000A		name-length
document-uri	document-uri	name
0x11		value-length
ftp://foo.com/foo	ftp://foo.com/foo	value
0x42	name type	value-tag
0x0008		name-length
job-name	job-name	name
0x0006		value-length
foobar	foobar	value
0x02	start job-attributes	job-attributes_tag
0x21	integer type	value-tag
0x0005		name-length
copies	copies	name
0x0004		value-length
0x00000001	1	value
0x03	start-data	data-tag
%!PS...	<PostScript>	data

## 482 10.5 Create-Job Request

483 The following is an example of Create-Job request with no parameters and no attributes

<b>Octets</b>	<b>Symbolic Value</b>	<b>Protocol field</b>
0x0100	1.0	version
0x0005	Create-Job	operation
0x01	<u>start operation-attributes</u>	<u>operation-attributes-tag</u>
0x47	<u>charset type</u>	<u>value-tag</u>
0x0012		<u>name-length</u>
attributes-charset	<u>attributes-charset</u>	<u>name</u>
0x0008		<u>value-length</u>
US-ASCII	<u>US-ASCII</u>	<u>value</u>
0x48	<u>natural-language type</u>	<u>value-tag</u>
0x001B		<u>name-length</u>
attributes-natural-language	<u>attributes-natural-language</u>	<u>name</u>
0x0005		<u>value-length</u>
en-US	<u>en-US</u>	<u>value</u>
0x03	start-data	data-tag

484 **10.6 Get-Jobs Request**

485 The following is an example of Get-Jobs request with parameters but no attributes.

<b>Octets</b>	<b>Symbolic Value</b>	<b>Protocol field</b>
0x0100	1.0	version
0x000A	Get-Jobs	operation
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
US-ASCII	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value
0x21	integer type	value-tag
0x0005		name-length
limit	limit	name
0x0004		value-length
0x00000032	50	value
0x44	keyword type	value-tag
0x0014		name-length
requested-attributes	requested-attributes	name
0x0006		value-length
job-id	job-id	value
0x44	keyword type	value-tag
0x0000	additional value	name-length
0x0008		value-length
job-name	job-name	value
0x03	start-data	data-tag

486 **10.7 Get-Jobs Response**487 The following is an of Get-Jobs response from previous request with 3 jobs. The Printer returns no information about the second  
488 job.

<b>Octets</b>	<b>Symbolic Value</b>	<b>Protocol field</b>
0x0100	1.0	version
0x0000	OK (successful)	status-code
0x01	start operation-attributes	operation-attribute-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
ISO-8859-1	ISO-8859-1	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-US	en-US	value

<b>Octets</b>	<b>Symbolic Value</b>	<b>Protocol field</b>
0x41	text type	value-tag
0x000E		name-length
status-message	status-message	name
0x0002		value-length
OK	OK	value
0x02	start job-attributes (1st object)	job-attributes-tag
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
fr-CA	fr-CA	value
0x21	integer type	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
147	147	value
0x42	name type	value-tag
0x0008		name-length
job-name	job-name	name
0x0003		name-length
fou	fou	name
0x02	start job-attributes (2nd object)	job-attributes-tag
0x02	start job-attributes (3rd object)	job-attributes-tag
0x21	integer type	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
148	148	value
0x13	compoundValue	value-tag
0x0008		name-length
job-name	job-name	name
0x0004		value-length
0x0002	2	value (number of values)
0x48	naturalLanguage	value-tag
0x0000	multi-value marker	name-length
0x0005		value-length
de-CH	de-CH	value
0x42	name type	value-tag
0x0000	multi-value marker	name-length
0x0003		name-length
isch guet	isch guet	name
0x03	start-data	data-tag

## 489 **11. Appendix B: Mapping of Each Operation in the Encoding**

490 The next three tables show the results of applying the rules above to the operations defined in the IPP model document. There is  
491 no information in these tables that cannot be derived from the rules presented in Section 3.8 "Mapping of Attribute Names".

492 The following table shows the mapping of all IPP model-document request attributes to an appropriate xxx-attribute-sequence or  
493 special position in the protocol.

494 The table below shows the attributes for operations sent to a Printer URI.

<b>Operation</b>	<b>operation attributes</b>	<b>job attributes</b>	<b>special position</b>
Print-Job	attributes-charset attributes-natural-language job-name document-name ipp-attribute-fidelity <del>document-charset</del> document-natural-language	job-template attributes	document-content
Create-Job or Validate-Job	attributes-charset attributes-natural-language job-name ipp-attribute-fidelity	job-template attributes	
Print-URI	attributes-charset attributes-natural-language job-name ipp-attribute-fidelity document-uri <del>document-charset</del> document-natural-language	job-template attributes	
Send-Document	attributes-charset attributes-natural-language job-id last-document document-name <del>document-charset</del> document-natural-language		document-content
Send-URI	attributes-charset attributes-natural-language job-id last-document document-name document-uri <del>document-charset</del> document-natural-language		
Cancel-Job	attributes-charset attributes-natural-language job-id message		
Get-Attributes (for a Printer)	attributes-charset attributes-natural-language requested-attributes document-format		
Get-Attributes (for a Job)	attributes-charset attributes-natural-language job-id requested-attributes		
Get-Jobs	attributes-charset attributes-natural-language limit requested-attributes which-jobs		

495 The table below shows the attributes for operations sent to a Job URI.



<b>Operation</b>	<b>operation attributes</b>	<b>job attributes</b>	<b>special position</b>
Send-Document	attributes-charset attributes-natural-language last-document document-name <del>document-charset</del> document-natural-language		document-content
Send-URI	attributes-charset attributes-natural-language last-document document-name document-uri <del>document-charset</del> document-natural-language		
Cancel-Job	attributes-charset attributes-natural-language message		
Get-Attributes (for a Job)	attributes-charset attributes-natural-language requested-attributes		

496 The following two tables shows the mapping of all IPP model-document response attributes to an appropriate xxx-attribute-  
497 sequence or special position in the protocol.

<b>Operation</b>	<b>operation attributes</b>	<b>job-attributes</b>	<b>unsupported-job-attributes</b>	<b>special position</b>
Print-Job, Print-URI, Create-Job, Send- Document or Send-URI	attributes-charset attributes-natural- language status-message	job-id job-uri job-state job-state-reasons job-state-message number-of- intervening-jobs	unsupported attributes	status-code
Validate-Job	attributes-charset attributes-natural- language status-message		unsupported attributes	status-code

498 Note: the unsupported-job-attributes are present only if the client included some job attributes that the Printer doesn't support.

499 Note: the job-attributes are present only if the server returns the status code of successful-ok or successful-ok-ignored-or-  
500 substituted-attributes.

<b>Operation</b>	<b>operation attributes</b>	<b>job-attributes</b>	<b>printer-attributes</b>	<b>special position</b>
Cancel-Job	attributes-charset attributes-natural- language status-message			status-code
Get-Attributes (of a job)	attributes-charset attributes-natural-	requested attributes		status-code

Operation	operation attributes	job-attributes	printer-attributes	special position
	language status-message			
Get-Attributes (of a printer)	attributes-charset attributes-natural- language status-message		requested attributes	status-code
Get-Jobs	attributes-charset attributes-natural- language status-message	requested attributes (see the Note below)		status-code

501 Note for Get-Jobs: there is a separate job-attribute-sequence containing requested-attributes for each job object in the response

## 502 12. Appendix C: Hints to implementors using IPP with SSL3

503 WARNING: Clients and IPP objects using intermediate secure connection protocol solutions such as IPP in combination with  
504 Secure Socket Layer Version 3 (SSL3), which are developed in advance of IPP and TLS standardization, might not be  
505 interoperable with IPP and TLS standards-conforming clients and IPP objects.

506 An assumption is that the URI for a secure IPP Printer object has been found by means outside the IPP printing protocol, via a  
507 directory service, web site or other means.

508 IPP provides a transparent connection to SSL by calling the corresponding URL (a https URI connects by default to port 443).  
509 However, the following functions can be provided to ease the integration of IPP with SSL during implementation.

510 connect (URI), returns a status.

511 “connect” makes an https call and returns the immediate status of the connection as returned by SSL to the user. The status  
512 values are explained in section 5.4.2 of the SSL document [ssl].

513 A session-id may also be retained to later resume a session. The SSL handshake protocol may also require the cipher  
514 specifications supported by the client, key length of the ciphers, compression methods, certificates, etc. These should be sent  
515 to the server and hence should be available to the IPP client (although as part of administration features).

516 disconnect (session)

517 to disconnect a particular session.

518 The session-id available from the “connect” could be used.

519 resume (session)

520 to reconnect using a previous session-id.

521 The availability of this information as administration features are left for implementors, and need not be standardized at this time